.193 DIA. HOLES (3) DRILL THRU 28B4162-86 (REF.) WHEN INSTALLING 28F7609 (REF.)

28F7609(1)
Q5106010-10 (4)
AC365D1032 (4)

REMOVE PAINT AROUND THIS HOLE ONLY 3/16 R

STBD.

FWD

CONTOUR STA. 2.0

CONTOUR STA. 2.5

28B4162-85 (REF.)

AMPLIFIER #CPR-50ABZ **

MOUNTING BASE #CPR50ABZ *
Q5106010-8 (16)
AC365D1032 (16)

28F7609 (REF.)

28B4162-86 (REF.)

28F7080-30 (REF.)

RECEIVER #CAY46AAM **

MOUNTING BASE #255043-502 *

28F7608 (4)
AN515-6-16 (16)
AC365-832 (16)

28B4162-87 (REF.)

28F7602 (REF.)

TYPICAL BONDING FOR EACH SHOCK MOUNTED BASE ON WOOD: 2 PLACES PER BASE. SEE NOTE #3. (A)

STA. 2.0

STA. 2.5

ATTACH BOND TO LOWER LORD MOUNT SCREW AS SHOWN (TYPICAL FOR AMPLIFIER)

** INDICATOR #CJP55AAZ

*#255044-501 - MOUNTING BASE
Q5106010-10 (16)
AC365D1032 (16)





H 422

NOTE:
1. ** DENOTES GOVERNMENT FURNISHED & GOVERNMENT INSTALLED EQUIPMENT
2. * DENOTES GOVERNMENT FURNISHED EQUIPMENT.
(A) 3. WHEN BASES ARE USED WHICH HAVE INTERNAL BONB IN LORD MOUNTS, BOND LORD MOUNTS TO TABLE BONDING STRIP WITH Q508A-4 BOND BRAID. ONE BONDBRAID FROM EACH LORD MOUNT TO BONDING STRIP

MCR270-6-1

PART NO.	QTY
**CAY46AAM RECEIVER	1
**CJP55AAZ INDICATOR	1
**CPR50ABZ AMPLIFIER	1
*CPR50ABZ AMPLIF. MTG. BASE	1
*255043-502 RECVR. MTG. BASE	1
*255044-501 INDIC. MTG. BASE	1
AC365-832	16
AC365D1032	36
Q508A-4 (SEE NOTE #3)	8
Q5106D10-10	20
AN515-6-16	16
Q5106D10-8	16
28F7608	4
28F7609	1

PARTS LIST PER ASSY.

B-29 / B-29A

SCALE 6" = 1'-0"

APPROVED FOR TOOLING BY

NAVY NONE

FINISH NONE

INSTALLATION - ASB - REMOTE INDIC. RECVR. & AMPLIFIER

OPP. HAND NONE

J 28F7610

R 28F7610